



ISO9001 ,14001,18001

TECHNICAL DATA SHEET

- PRODUCT** : Lead Based Compound Stabilizer For PVC Ceiling, Wall Cover, Curtain Rod...
- GRADE** : IRSTAB PFL – 303A
- PACKING** : 25 kgs net multiwall plastic bags
- TYPICAL USE** : Depending on the formulation, processing condition and the type of products, it varies in the range of 1.8 – 2.5 phr.

SPECIFICATION

Appearance	: Off White Flake
Particle Size (%)	: 95 ± 2
Specific Gravity	: 2.00 to 2.30
Mixed Metal Content as PbO (%)	: 22 ± 1.0
Bulk Density	: 600 ± 10 g/l
Moisture Content (%)	: 1% Max.
Soft. Point (°C) or MP	: >75° C

APPLICATION

The above product is lead based compound stabilizer containing light Lead based compound, antioxidant, internal and external lubricants, which is applicable for U-PVC panel extrusion, ceiling and etc. It is dust-free and produced based on a newest formula in the world as well as based on the international standards.

This product has good thermo stability and processing performance, reasonable formulation. It has excellent internal and external lubricating balance; do not need any more lubricant. It contains proper composite antioxidant and macromolecule auxiliaries, which can obviously improve the mechanical property and surface quality of PVC panel and final production.